

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 616 027 A1

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 93870215.6

(22) Date of filing: 16.11.93

(51) Int. Cl.⁵: **C11D 1/00, C11D 1/722,**
C11D 1/72, C11D 1/14,
C11D 1/825, C11D 1/83

(30) Priority: 19.03.93 EP 93870050
07.07.93 EP 93870126

(43) Date of publication of application:
21.09.94 Bulletin 94/38

(84) Designated Contracting States:
AT BE CH DE DK ES FR GB GR IE IT LI LU NL
PT SE

(71) Applicant: **THE PROCTER & GAMBLE**
COMPANY

One Procter & Gamble Plaza
Cincinnati Ohio 45202 (US)

(72) Inventor: **Evers, Marc François Theophile**
Jozef Van Elewyckstraat 26 B8
B-1853 Grimbergen (BE)

Inventor: **Geboes, Peter Rosalia Joannes**
Kapellestraat 230
B-2630 Aartselaar (BE)

Inventor: **Michael, Daniel Wayne**
10631 Stargate Lane
Cincinnati, Ohio 45240 (US)

Inventor: **Morini, Massimo**
Rue Edouard Faes 46
B-1090 Jette (BE)

Inventor: **Policicchio, Nicola John**
2 Nivem Place
Brampton, Ontario (CA)

Inventor: **Reniers, Vincent**
Zijdelingsestraat 19
B-3300 Tienen (BE)

Inventor: **Scott, Louise Gail**
Stijn Streuvelsstraat 9
B-1933 Sterrebeek (BE)

(74) Representative: **Engisch, Gautier et al**
Procter & Gamble
European Technical Center N.V.
Temselaan 100
B-1853 Strombeek-Bever (BE)

(54) **Concentrated cleaning compositions.**

(57) Stable and clear concentrated cleaning compositions are disclosed which comprise at least one short chain surfactant. The short chain surfactants allow for the formulation of stable compositions without the need for additional stabilizers, and the short chain surfactants are effective in cleaning, especially greasy cleaning.

EP 0 616 027 A1

Technical Field

The present invention relates to concentrated cleaning compositions. Although the present invention relates primarily to cleaning compositions for hard surfaces, it may also be of interest for other cleaning compositions including dishwashing and laundry detergent compositions.

Background of the Invention

Concentrated cleaning compositions are well known in the art. Concentrated compositions are mainly characterized by the fact that they comprise a higher concentration of active ingredients compared to a conventional cleaning composition, and a problem which is typically encountered when formulating concentrated cleaning compositions is therefore the physical stability of such compositions. Indeed, because such compositions comprise a high amount of active ingredients in a limited amount of water, stability problems appear which lead, if not solved, to compositions which separate into several phases. This phenomenon affects the performance of the composition and is visually noticeable, thereby rendering such formulations unfit for commercialization.

Various solutions have been proposed to solve this problem which typically involve the use of specific stabilizing ingredients, or hydrotropes. Such ingredients have the sole function of stabilizing the composition. They thus increase the cost of formulating such compositions without providing any cleaning performance benefits, and they furthermore require to free up parts in the formulation which could otherwise be used to formulate more actives.

For instance, EP 316 726 discloses concentrated compositions in the form of microemulsions which comprise water, perfume, a surfactant and a so-called co-surfactant. The co-surfactant is said to reduce the interfacial tension at interfaces between dispersed and continuous phases of an emulsion of said surfactant, thereby creating a stable microemulsion. The so-called co-surfactants in the '726 publication are listed as specific glycol ethers, which are traditionally regarded as solvents in this field, or specific carboxylic acids. The co-surfactants in the '726 publication do not appear to participate to the overall cleaning performance of the product.

It is therefore an object of the present invention to formulate a stable concentrated cleaning composition without using ingredients which are provided for the sole purpose of providing stability to the compositions herein, but which also participate significantly to the cleaning performance of said compositions.

It has now been found that this object can be met by formulating a concentrated aqueous compositions comprising at least one short chain surfactant, i.e. with a hydrophobic group consisting of a C₆-C₁₀ alkyl chain, said compositions not being in the form of microemulsions. Said short chain surfactants provide stability to the compositions herein and, in the same time, significantly boost the overall cleaning performance, especially grease cleaning, both in neat and dilute usage.

Summary of the Invention

The compositions herein are stable clear concentrated cleaning compositions comprising from 10 % to 80 % by weight of the total composition of water and at least one short chain surfactant comprising a C₆-C₁₀ alkyl chain as its hydrophobic portion. The compositions herein are preferably not in the form of microemulsions.

Detailed Description of the Invention

The compositions of the present invention are concentrated aqueous compositions. By concentrated, it is meant herein that the compositions comprise from 10 % to 90 % by weight of the total composition of water, preferably from 15 % to 75 %, most preferably from 30 % to 80 %.

The compositions according to the present invention are clear and stable. By clear and stable, it is meant herein that the compositions of the present invention are macroscopically substantially transparent, in the absence of any opacifier, and that said compositions do not macroscopically separate into separate phases during at least 1 month, at temperatures ranging from 4 °C to 50 °C, upon standing.

The compositions according to the present invention further comprise at least one short chain surfactant, or mixtures thereof. All surfactants have in common that they comprise a hydrophobic portion and a hydrophilic portion. By short chain surfactant, it is meant herein surfactants which comprise a C₆-C₁₀ alkyl chain as their hydrophobic portion. Such short chain surfactants are accordingly those conventionally used in this field, but with a shorter alkyl chain, and can be of any type. Accordingly, suitable short chain

surfactants for use herein include C_6 - C_{10} alkyl sulfates (C_6 - $C_{10}SO_4$), alkyl ether sulfates (C_6 - C_{10} -(OCH_2CH_2) $_eSO_4$), alkyl sulfonates (C_6 - $C_{10}SO_3$), alkyl succinates (C_6 - $C_{10}OOCCH_2CH_2COOZ$), alkyl carboxylates (C_6 - $C_{10}COOM$), alkyl ether carboxylates (C_6 - $C_{10}(OCH_2CH_2)_eCOOM$), alkyl sarcosinates (C_6 - $C_{10}CON-(CH_3)R$), alkyl sulfo succinates (C_6 - $C_{10}OOCCH(SO_3M)CH_2COOZ$), amine oxides (C_6 - $C_{10}RR'NO$), glucose amides (C_6 - $C_{10}CONR''X$), alkyl pyrrolidones (C_6 - $C_{10}(C_4H_6ON)$), alkylpolysaccharides (C_6 - $C_{10}OGg$), alkyl alkoxyates (C_6 - $C_{10}(OCH_2CH_2)_e(OCH_2CH_2CH_2)_pOH$) and betaines (C_6 - $C_{10}N^+(CH_3)_2CH_2COO^-$). In the formulae in brackets, e and p are independently from 0 to 20 and $e+p>0$, Z is M or R, M is H or any counterion such as those known in the art, including Na, K, Li, NH_4 , amine, X is a polyhydroxyhydrocarbyl having a linear hydrocarbyl chain with at least 3 hydroxyls directly connected to the chain, or an alkoxyated derivative thereof, R, R' and R'' are C_1 - C_5 alkyl groups, possibly functionalized with hydroxyl groups, R and R' are preferably C_1 - C_3 , most preferably methyl, R'' is preferably 2-hydroxyethyl or 2 hydroxypropyl, G is a saccharide, preferably glucose, and g is of from 1.5 to 8. All these surfactants are well known in the art. A more complete disclosure of conventional glucose amides can be found for instance in WO 92-06154 and a more complete disclosure of conventional alkyl polysaccharides can be found for instance in US 4,536,319.

The compositions according to the present invention may comprise any of the above surfactants alone, or any combination thereof, depending on the end use envisioned.

Preferred short chain nonionic surfactants for use herein are alkyl alkoxyates according to the formula C_6 - $C_{10}(OCH_2CH_2)_e(OCH_2CH_2CH_2)_pOH$, where e and p representing respectively the degree of ethoxylation and propoxylation, are independently of from 0 to 20, and that $e+p>0$. Most preferred short chain nonionic surfactants for use herein are those where e and p are such that $e+p$ is from 3 to 10, particularly those where p is 0 and e is from 3 to 8. Also, most preferred short chain nonionic surfactants for use herein are those where said short chain is a hydrocarbon chain comprising from 7 to 10 carbon atoms. Said preferred short chain nonionic surfactants for use herein can be manufactured by the processes well known to the man skilled in the art, such as condensation of the corresponding alcohol and alkylene oxide, but such short chain surfactants are more conveniently commercially available for instance from Sidobre under the trade name Mergital®C4 (C8EO4), from Kolb under the trade names Imbentin® AG/810/050 and AG/810/080 (respectively C8-10EO5 and C8-10EO8).

Preferred short chain anionic surfactants for use herein are C_6 - C_{10} alkyl sulfates (C_6 - $C_{10}SO_4$) and alkyl sulfonates (C_6 - $C_{10}SO_3$). Most preferred are the C6-C8 alkyl sulfates and sulfonates. The alkyl sulfonates can provide products with less filming/streaking, as demonstrated hereinafter, as compared to other anionics such as alkyl sulfates. Such short chain anionic surfactants can be made by well known sulphation or sulphonation processes followed by neutralization, but said anionic short chain surfactants are more conveniently commercially available, for instance from Rhone Poulenc under the trade name Phodapon® OLS, or from Witco under the trade name Witconate®.

The compositions according to the present invention may comprise from 0.1 % to 50 % by weight of the total composition, preferably from 1% to 40%, most preferably from 1.5% to 30% of said short chain surfactants. It has been found that said short chain surfactants allowed the formulation of concentrated compositions without the need for any stabilizing systems, or certain formulation type such as microemulsions. Said short chain surfactants are also particularly effective in cleaning, especially grease cleaning.

The compositions according to the present invention may comprise short chain surfactants only, or combinations of short chain surfactants with conventional longer chain surfactants. Accordingly, suitable long chain surfactants for use herein include those listed herein above in the description of short chain surfactants, but with a longer alkyl chain, of from C_{11} - C_{24} . Preferred long chain surfactants for use herein are long chain alkyl sulfonates, e.g. paraffin sulfonates and alkyl ethoxyates, and mixtures thereof.

If combinations of short chain and long chains are used, it is preferred to observe certain ratios: if short chain anionic surfactants are used, it is preferred to observe a minimum weight ratio of short chain anionic surfactant to longer chain surfactant of 1:10. If short chain nonionic surfactants are used, it is preferred to observe a minimum weight ratio of short chain nonionic to longer chain surfactant of 1:5.

Depending on the end use envisioned, the compositions herein may further comprise a variety of other optional ingredients including builders, alkanolamines, pH adjusting agents, perfumes, dyes, bleaches, enzymes and the like. When an alkalinity source is present, it is desirable that the potassium cation be used, E.g., when potassium carbonate is used instead of sodium carbonate, as demonstrated hereinafter, there is less filming/streaking. As used herein, potassium carbonate comprises potassium bicarbonate.

In some instances, it may be appropriate to include a suds suppressing system in the compositions herein. Said suds suppressing system can advantageously be a mixture of 2-alkyl alkanols as described for instance in DE 40 21 265, or mixtures thereof, with a C_8 to C_{22} fatty acid, or mixtures thereof. Such a system is particularly advantageous as both ingredients appear to act in synergy. Thus even a very low amount of said system is enough to control suds efficiently. Accordingly, said system is present in amounts

of from 0.1% to 5% by weight of the total composition, preferably 0.5% to 3%.

The compositions herein do not require the presence of a stabilizing compound. By stabilizing compound, it is meant herein a compound whose sole function is to enhance the physical stability of the composition. Such compounds are typically xylene or toluene sulphonate salts, and glycol ethers, including ethylene glycol monobutyl ether, diethylene glycol monobutyl ether, dipropylene glycol monobutyl ether, dipropylene glycol methyl ether, propylene glycol methyl ether, tripropylene glycol methyl ether, propylene glycol monobutyl ether and other various solvents such as ethanol and butanol. Accordingly, the compositions of the present invention are preferably substantially free of such stabilizing compounds.

The present invention further encompasses a method of cleaning a hard surface which comprises the steps of diluting a composition according to the preceding claims in water, then applying it to said hard surface. Depending on the exact formulation, the compositions herein may be used both neat and diluted from 10 to 500 times.

Particularly preferred compositions contain: (1) from 5% to 30% of short chain surfactant, preferably a mixture of (a) short chain nonionic surfactant having the formula $C_{6-10}(EO)_c(PO)_pOH$ wherein EO is an ethoxy moiety, PO is a propoxy moiety with each c and p being from 0-20, preferably from 3 to 10, more preferably c being from 3 to 8 and p being 0 and (b) C_{6-10} alkyl sulfonate, (2) optional, but preferred, long chain nonionic surfactant, preferably nonionic $C_{12-16}(EO)_n$, preferably a mixture of nonionic surfactants in which one has an n of from about 2 to about 10 and the other has an n of from about 20 to about 60; (3) optional hydrophobic cleaning solvent, preferably $C_{2-6}(EO)_x(PO)_yOH$ wherein x and y are each from 0 to about 2, and more preferably $C_4(EO)_2OH$; (4) optional, but preferred, fatty acid suds suppressant at a level of from 0.1% to 1%, preferably from 0.2% to 0.8%; (5) optional, but preferred, C_{12-18} fatty alcohol, more preferably branched chain fatty alcohols such as 2-butyl octanol and/or 2-hexyl decanol; and (6) optional, but preferred, alkalinity source, more preferably potassium carbonate. The balance of each composition is preferably an aqueous solvent system.

The present invention will be further illustrated by the following examples.

Examples

The following compositions are made by mixing the listed ingredients in the listed proportions.

30

35

40

	I	II	III	IV
$C_{13/15}$ alkyl ethoxylate EO_3	3	-	3	-
$C_{12/15}$ alkyl ethoxylate EO_{30}	5	5	-	-
C_8 alkyl sulfate	-	10	10	-
C_8 alkyl sulfonate	-	-	-	20
C_8 alkyl ethoxylate EO_6	-	9	-	-
$C_8/10$ alkyl ethoxylate EO_5	-	-	-	20
Citric acid	3	3	1	-
Monoethanolamine	3	3	1	1
Triethanolamine	-	-	3	-
Water & minors	————up to 100%————			

45

All compositions were evaluated for their physical stability at 4°C, at room temperature (20°C), and at 50°C. Composition I, which is not within the invention, was a gel at 4°C, and an emulsion at room temperature and at 50°C. All other compositions, within the invention, were clear transparent liquids in the same conditions.

50

Other compositions were made by mixing the listed ingredients in the listed proportions.

55

	V	VI	VII	VIII
C13/15 alkyl ethoxylate EO3	4	3	5	1
C13/15 alkyl ethoxylate EO7	-	3	-	5
C7-9 alkyl sulfate	7.5	-	-	-
C8 alkyl sulfate	-	8	-	10
C8 alkyl sulfonate	-	-	10	-
C7-9 alkyl ethoxylate EO6	-	-	10	5
C8-10 alkyl ethoxylate EO5	10	9	-	9
C13/15 alkyl ethoxylate EO30	6	4	3	5
Na Paraffin Sulfonate	-	5	-	-
Citric acid	3	-	-	3
Sodium carbonate	-	3	-	-
2-hexyl decanol	1	0.6	1	-
Palm Kernel Fatty Acid	0.4	0.4	1	-
Water & minors	————up to 100%————			

The invention is illustrated by the following examples. All values in table are weight percentages.

Example No.:	1	2	3
Ingredient	Wt%	Wt%	Wt%
Sodium Octyl Sulfate	7.0	-	-
Sodium Octyl Sulfonate	-	7.0	7.0
Alfonic R 810-65 (C ₈₋₁₀ EO ₆ average)	10.0	10.0	10.0
Neodol R 23-3 (C ₁₂₋₁₃ EO ₃)	4.0	4.0	4.0
Lutensol R AO-30 (C ₁₃₋₁₅ EO ₃₀)	6.0	6.0	6.0
Sodium Carbonate	-	2.0	-
Potassium Carbonate	2.0	-	2.0
Palm Kernel Fatty Acid	0.4	0.4	0.4
2-Butyl Octanol	0.4	0.4	0.4
Hydrophobic Perfume*	1.5	1.5	1.5
Deionized Water and Minors	q.s.	q.s.	q.s.
pH	10.8	10.8	10.8
Alfonic is a trade name used by Vista Chemical. Neodol is a trade name used by Shell Chemical Co. Lutensol is a trade name used by BASF Corp.			

*Hydrophobic perfume consists of terpenes, terpene alcohols, and other perfume materials which are typically insoluble in water.

The invention is also illustrated by the following Examples. All values in table are weight percentages.

Example No.:	4	5
Ingredient	Wt%	Wt%
5 Sodium Octyl Sulfonate	7.0	7.0
Alfonic R 810-65 (C ₈₋₁₀ EO ₆ average)	10.0	10.0
Neodol R 23-3 (C ₁₂₋₁₃ EO ₃)	4.0	4.0
10 Lutensol R AO-30 (C ₁₃₋₁₅ EO ₃₀)	6.0	6.0
Diethylene Glycol	3.0	-
Monobutyl Ether		
Potassium Carbonate	2.0	2.0
15 Palm Kernel Fatty Acid	0.4	0.6
2-Butyl Octanol	0.4	-
Hydrophobic Perfume*	1.5	1.5
Deionized Water and Minors	q.s.	q.s.
20 pH	10.5	10.5
Alfonic is a trade name used by Vista Chemical. Neodol is a trade name used by Shell Chemical Co. Lutensol is a trade name used by BASF Corp.		

*Hydrophobic perfume consists of terpenes, terpene alcohols, and other perfume materials which are typically insoluble in water.

Filming/Streaking data were obtained on the above Examples.

Filming/Streaking Test Method -Dilute (No Wax Floors)

Materials

1. Spontex cellulose sponges (cut to 2"x4"x1")
2. No wax floor tiles (12"x12")
3. Test products - these are diluted with heated tap water that has been adjusted to a hardness of 7 grains and maintained at 110°F. Dilution is 1 part test product:128 parts water.

Procedure:

1. Clean the floor tiles with tap water using a sponge. Then rinse with distilled water and dry with paper towels. Apply a small amount of isopropyl alcohol to each tile and dry thoroughly.
2. Clean sponges of all factory preservatives and rinse well. Use the same sponge for the entire test, rinsing well between change of products. Soak the sponge in the product being tested.
3. Transfer 15 mls of the diluted test product into an inverted sponge carrier.
4. Squeeze out excess product from the sponge and dip the sponge evenly on the flat surface of the carrier, gently squeezing down to soak up the product into the sponge. Tare the sponge on a 2-place balance, product side up.
5. One tile is used per replicate. The sponge is wiped lightly over the tile surface by drawing an "M" pattern which covers the entire tile as much as possible. Then another "M" is drawn sideways. Place the sponge on the tared balance and record the amount of product applied to the tile.
6. Three replicates are used for each product tested.
7. Tiles are air dried in air with 52% relative humidity at room temperature (about 24°C) for approximately one hour.
8. Three expert graders grade the panels on the following scale system:
 - 0 = no filming/streaking
 - 6 = very poor filming/streaking
 Grades are averages for each product.

Filming/Streaking Data

Formula No.	Filming/Streaking Mean Grade
3	1.4
2	1.8
1	2.1

The LSD for this test was 0.2 at the 95% Confidence Interval, therefore the Filming/Streaking mean values achieved for each formula are statistically distinct from one another. The superior Filming/Streaking result was achieved through a combination of both the octyl sulfonate (3 vs 1) and the potassium carbonate (3 vs 2).

Claims

1. A stable and clear concentrated cleaning composition comprising from 10 % to 80 % by weight of the total composition of water and at least one surfactant, **characterized in** that said surfactant is a short chain surfactant comprising a C₆-C₁₀ alkyl chain as its hydrophobic portion, and said composition is not in the form of a microemulsion.
2. A composition according to claim 1 wherein said short chain surfactant represents from 0.1 % to 50 % by weight of the total composition, preferably from 1 % to 40%, most preferably from 1.5% to 30%.
3. A composition according to the preceding claims wherein said short chain surfactant, or mixtures thereof is :
 - a nonionic surfactant according to the formula C₆-C₁₀(OCH₂CH₂)_e(OCH₂CH₂CH₂)_pOH, where e and p representing respectively the degree of ethoxylation and propoxylation are independently of from 0 to 20, and that e + p > 0; or
 - an anionic surfactant according to the formula C₆-C₁₀SO₄ or C₆-C₁₀SO₃; or
 - Mixtures thereof.
4. A composition according to claim 3 wherein e and p are such that e + p is from 3 to 10, preferably p is 0 and e is from 3 to 8.
5. A composition according to claim 3 wherein said anionic surfactant is C₆-C₁₀SO₄ or C₆-C₁₀SO₃.
6. A composition according to any of the preceding claims which comprises from 30% to 70% by weight of the total composition of water.
7. A composition according to any of the preceding claims which further comprises a long chain surfactant comprising a C₁₁-C₂₄ alkyl chain in its hydrophobic portion.
8. A composition according to claim 7 which comprises an anionic short chain surfactant and the weight ratio of said short chain surfactant to said long chain surfactant is at least 1:10.
9. A composition according to claim 7 which comprises a nonionic short chain surfactant and the weight ratio of said short chain surfactant to said long chain surfactant is at least 1:5.
10. A composition according to claim 7-9 wherein said long chain surfactants are selected from long chain alkyl sulfonates and long chain alkyl ethoxylates, and mixtures thereof.
11. A composition according to any of the preceding claims which is substantially free of stabilizing compounds.
12. A composition according to any of the preceding claims which comprises from 0.1% to 5% by weight of the total composition, preferably 0.5% to 3% of a suds suppressing system, said suds suppressing

system comprising a 2-alkyl alkanol, or mixtures thereof and a C₈-C₂₂ fatty acid, or mixtures thereof.

13. A method of cleaning a hard surface which comprises the steps of diluting a composition according to the preceding claims in water, then applying it to said hard surface.

5

14. A composition according to any of the above claims containing, as an additional ingredient, from about 1% to about 4% potassium carbonate.

10

15. A composition according to any of the above claims wherein said short chain surfactant is C₆₋₁₀ alkyl sulfonate.

15

20

25

30

35

40

45

50

55



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 87 0215

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.5)
X	WO-A-92 02604 (HENKEL) * claims 1-3,7,8 * ---	1-8	C11D1/00 C11D1/722 C11D1/72
X	DE-A-39 43 070 (HENKEL) * page 2, line 66 - page 4, line 4; claims 1-6; example 4 * ---	1-3,5,7,13	C11D1/14 C11D1/825 C11D1/83
X	FR-A-2 345 513 (RHONE-POULENC-INDUSTRIES) * claims 1-9,11 * ---	1-4,6,7,9,10	
X	FR-A-2 247 531 (THE PROCTER & GAMBLE CO.) * page 9, line 1 - page 14, line 38; claim 1; example 5 * ---	1-4,6,7,10	
X	FR-A-2 550 959 (DIVERSEY CORP.) * claims; example 8 * ---	1-4	
X	GB-A-2 011 944 (UNILEVER) * the whole document * ---	1-4,6,7,10	TECHNICAL FIELDS SEARCHED (Int.Cl.5) C11D
X	EP-A-0 213 554 (HENKEL) * claims 1,9; example 1 * ---	1-4,6	
X	EP-A-0 125 854 (THE PROCTER & GAMBLE CO.) * page 10, line 7 - line 9; claims; examples 1,3 * ---	1-4,6,7,9	
X	FR-A-2 339 672 (THE PROCTER & GAMBLE CO.) * page 3; claims 1,17; example 3 * ---	1-4	
X	GB-A-1 462 134 (THE PROCTER & GAMBLE CO.) * claims 1-17; example IV * ---	1-4,6,7,10	
-/--			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 17 June 1994	Examiner Serbetsoglou, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document I : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document			

EPO FORM 1503 (04.92) (P04001)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 87 0215

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 5)
X	US-A-4 772 415 (ADONE) * column 3, line 21 - line 41; claims 1-3, 11 *	1-4	
X	FR-A-2 207 981 (BASF) * page 9, line 18 - line 21; claim 1; examples 6, 8, 9, 13-16 *	1-4, 6, 7, 10	
X	EP-A-0 244 006 (UNILEVER) * claims 1, 2; example 1 *	1-4, 6, 7, 10	
X	EP-A-0 496 188 (THE PROCTER & GAMBLE CO.) * page 3, line 36 - page 4, line 45; claims 1, 5; examples *	1-4, 7, 10	
P, X	WO-A-93 15172 (HENKEL) * page 5, line 5 - line 8; claims 1-11; examples *	1-3, 5-7, 10, 14	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 5)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 17 June 1994	Examiner Serbetsoglou, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document			